

HILEC 547R SUPERSTRETCH

EXPANDABLE SILICONE RUBBER COATED FIBERGLASS SLEEVING

THERMAL CLASS: 200°C
NEMA TF-1, Type 5

MIL-I-3190/6 (grade A)
UL FILE E123956 (grade A)

DESCRIPTION

547R SUPERSTRETCH is comprised of a two-component liquid silicone rubber continuously applied to expandable fiberglass braid. This construction allows the sleeving to be expanded to over twice its relaxed diameter. **547R SUPERSTRETCH** provides superior expandability while retaining excellent physical and electrical properties over a wide range of temperatures (-55°C to +200°C).

RECOMMENDED USE

547 SUPERSTRETCH is recommended for sleeving applications that require a snug fit over irregular shapes. It has the capability to provide a "heat shrink"-like fit while still exhibiting flexibility, abrasion resistance, moisture resistance, cut-through resistance and chemical resistance.

PHYSICAL PROPERTIES (coating)

Hardness	30 durometer, shore A	Resistance to:	
Tensile Strength	>1000 psi	Ozone	Excellent
Elongation	>600 %	Corona	Excellent
100% Modulus	300 psi	Radiation	Excellent
Tear strength	150 ppi	Sunlight	Excellent
Compression set	>8.0% (22 hrs @ 177°C)	Fungus	Excellent

DIELECTRIC GRADE	PRODUCT NUMBER	MIN. AVE. BREAKDOWN	MIN. INDIV.
A	547RSS	8000	6000

AVAILABILITY

- **SIZES:** **547R SUPERSTRETCH** is available in continuous spooled lengths or cut lengths in 8 various sizes designed to cover NEMA #13 through 1" I.D. (see reverse).
- **COLORS:** **547R SUPERSTRETCH** is available in black and white. Other colors may be available subject to minimum quantities and/or set-up charges.

The above data is informational only and should not be used for specification purposes. 11/01

Phone: (585) 492-2212 • Fax: (800) 450-8193
Email: info@hilec.com • Website: www.hilec.com